


- 1.1 Lawn, perennials, shrubs and small trees.
- 1.2 System substrate 'Roof Garden', depth: ≥ 200 mm.
For total substrate depth exceeding 350-400 mm:
in project specific combination with mineral sub-substrate 'Zincolit Plus'
- 1.3 Filter Sheet TG
- 1.4 Drainage element Stabilodrain® SD 30
- 1.5 Protection Mat ISM 50
- 1.6 Roof construction with root-resistant waterproofing

- 2.1 Concrete L-curb
- 2.2 Concrete foundation for supporting structure

- 3.1 Concrete paving slab
- 3.2 Bedding layer, stone chippings, 30 - 50 mm
- 3.3 Gravel base layer, compacted
- 3.4 Filter Sheet PV
- 3.5 Drainage element Stabilodrain SD 30, evaporation holes facing down, filled with bedding material, see 3.2



PLEASE NOTE:

THIS DETAILED SOLUTION MAINLY REFERS TO THE GREEN ROOF SYSTEM. THE ROOF CONSTRUCTION IS ONLY SCHEMATIC. THE DIMENSIONS SHOWN ARE REQUIRED DIMENSIONS FOR THE ZINCO GREEN ROOF SYSTEM. IN SOME CASES, LOCAL CODES AND STANDARDS MAY REQUIRE GREATER DIMENSIONS FOR A PARTICULAR APPLICATION. THE DESIGNER / PLANNER MUST VERIFY COMPLIANCE WITH LOCAL CODES AND STANDARDS.



	Issued on: 08.01.2014	System: 'Landscaped Underground Garage' with Stabilodrain® SD 30	Drawing title: Foundation for supporting structure	Drawn by: pbi
	Modified: 08.01.2015 11:09		Job title: -STANDARD ARCHITECTURAL DETAIL-	Scale: 1:5
	File: CAD_en_LUG_SD30_Fr_Det11.dwg	Subject to technical alterations and printing errors; Authorized by ZinCo GmbH, 72622 Nuertingen, Germany Tel. ++49/7022/6003-100 Fax ++49/7022/6003-100, e-mail: info@zinco-greenroof.com, www.zinco-greenroof.com		