

"Walk- and Driveway" with Stabilodrain® SD 30

Detail:
Roof Outlet with Heavy Duty Inspection Chamber

System build-up

- 1.1 Paving, e.g. concrete pavers
Depth: ≥ 100 mm for cars up to 3 t
≥ 120 mm for lorries up to 16 t
≥ 140 mm for lorries exceeding 16 t
- 1.2 Bedding layer, stone chippings, poor in lime, 30-50 mm
- 1.3 Compacted base layer, e.g. gravel, poor in lime
Depth: ≥ 150 mm for cars up to 3 t
≥ 200 mm for lorries up to 16 t
≥ 250 mm for lorries exceeding 16 t
- 1.4 Filter Sheet PV
- 1.5 Stabilodrain® SD 30, filled with stone chippings (see 1.2)
- 1.6 Filter Sheet PV
- 1.7 Roof construction with suitable water proofing

Note:


The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

-

Version:	Reviewed:	Scale:	Size:
28.11.2018 PBi/ EVo	-	none	A 4

Entw01_G+F_SD30_Fd0.dwg



- 2.1 Heavy Duty Inspection Chamber BES 300 with
 - 2.1.1 Sand trap
 - 2.1.2 Filter sheet collar
- 2.2 Elastodrain® EL 202-Support Board
- 2.3 Roof outlet

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2,
72622 Nuertingen/ Germany; Tel: +49/7022-6003-0
info@zinco-greenroof.com; www.zinco-greenroof.com

Subject to technical alterations and printing errors.

