
Subject to technical alterations and printing errors • First edition 09/2007; Revised 01/2012

Product Data Sheet Protectodrain® PD 250



Heavy duty drainage element with incorporated protection properties for the use in intensive green roof applications or in hard landscape applications.



Technical Data

Protectodrain® PD 250

Heavy duty drainage element made of ABS (Acrilonitrile Butatiene-Styrene) with attached rubber protection mat on the under side and lateral step joint.

Compressive strength at 10%

compression (EN ISO 25619-2): ca. 460 kN/m²

In-plane water flow capacity (EN ISO 12958):

Dimensions: ca. 1.00 x 2.00 m


Accessories: Rubber 2-hole Connector (1 piece is required per meter joint)

Features

- driveable by wheel loaders
- attached rubber protection mat provides mechanical protection for the waterproofing
- · low in weight
- economic installation process
- high drainage capacity tested according to EN ISO 12958
- connection of butt jointed elements possible by special connecting pieces
- plastic studded sheet and rubber protection mat can be easily separated for recycling
- joint connector as accessory available

Application Example

"Underground Car Park"



Plant layer

System Substrate "Roof Garden"

Zincolit® Plus Filter Sheet TG Protectodrain® PD 250 Slip Sheet TGF 20

Roof construction with root resistant waterproofing

Specification Suggestion

Heavy duty drainage element made of ABS plastic with attached rubber protection mat on the underside, Height ca. 25 mm, Stud height ca. 20 mm, Compressive strength at 10% compression according to EN ISO 25619-2 ca. 460 kN/m², in-plane water flow capacity

tested according to EN ISO 12958, delivery and installation according to manufacturer's instructions.

Make: ZinCo Protectodrain® PD 250 Enquiries: ZinCo GmbH.

Phone: +49 7022 6003-0

